



KFLT2 FUEL LUBE TRUCK

66,000 GVWR & 140" CT

*Specifications subject to change without notice

// BODY

Knapheide Fuel & Lube Body

- Galvanneal steel body construction
- Body is immersed in Knapheide's electrodeposition prime paint system for superior corrosion resistance
- ICC lights and reflectors included on body
- Grab handles, split cabinet design with dual roll-up doors and rear center access steps with grab handles
- Control panel located in the reel compartment with switches to control pumps, lighting systems, and air compressor
- Underbody storage compartments on each side of the body under fuel tank, compartments include over center door retainers for elimination of involuntary swing and stainless steel, paddle-activated rotary latches
- Diesel tank direct mounts to the truck frame
- Product tanks mounted to an innovative platform side rail using isolators which isolates twisting and vibration to eliminate tank fractures
- 20 lb. fire extinguisher installed in reel compartment

// DIESEL SYSTEM

2,000 Gallon capacity diesel tank

- Tank design is a modified ellipse style with 3/16" steel wall construction with flat panel in center for graphics
- Emergency shut-off, roll over protection system, and (2) lift hooks located on top of the tank included
- (2) Hannay 50' x 1" spring retractable hose reels
- (1) 4 digit analog fuel meter with re-zeroing feature

// FRESH OIL TANKS

(1) 100 Gallon capacity oil tanks

- Steel construction with vented fill cap and replaceable sight gauges
- Graco 5:1 operated product pump with product filter and thermal relief
- 50' x 1/2" spring rewinding hose reel with mechanical meter dispense nozzle

(2) 50 Gallon capacity oil tanks

- Steel construction with vented fill cap and replaceable sight gauges
- Graco 5:1 operated product pump with product filter and thermal relief
- 50' x 1/2" spring rewinding hose reel with mechanical meter dispense nozzle

// SALVAGE OIL SYSTEM

(1) 250 Gallon capacity salvage oil system

- Steel construction with vented fill cap and replaceable sight gauges
- Graco 1050 air operated diaphragm pump with reversion valve
- 30' x 1" spring rewind hose reel

// NEW COOLANT TANK

(1) 100 Gallon capacity tank

- 304 Stainless steel construction with vented fill cap and replaceable sight gauges
- Graco 716 air operated diaphragm pump
- 50' x ½" spring rewind hose reel

// USED COOLANT TANK

(1) 100 Gallon capacity tank

- Steel construction with vented fill cap and replaceable sight gauges
- Graco 716 air operated diaphragm pump
- 50' x ½" spring rewind hose reel

// GREASE DRUM

(1) 400 lb. grease drum

- Graco 50:1 air operated shovel pump with 50' x 3/8" high pressure grease reel and standard grease nozzle
- Drum tie down kit included

// AIR COMPRESSOR

35 CFM (100 PSI) Compressor

- Reciprocating air compressor with FLR system
- 20 Gallon air tank and 50' x ½" spring rewind hose reel

// LIGHTING

All lighting meets FMVSS 108 regulations

- LED S/T/T lights, backup lights, and marker lights
- LED compartment lights in hose reel compartment and underbody compartments
- (4) adjustable work lights