

# KNAPHEIDE STEEL GOOSENECK BODIES





#### **GOOSENECK TURNOVERBALL HITCH**

A B&W Turnoverball\*, rated at 30,000 lbs. gross trailer weight, with 7,500 lb. tongue weight. Currently in all PGT models.

#### **STEEL GOOSENECK BODIES**

Versatility with storage solutions to meet every need, Knapheide Gooseneck Bodies are an easy choice. Rugged construction, enhanced styling and secure storage give you a body that can haul it all.

Reliable offerings range from the mid-level PGTB, skirted PGTC, the deluxe PGTD and PGTE.

#### **POPULAR VOCATIONS**





PGTC
GOOSENECK BODIES

PGTC-ITIO
\*Body may be shown with optional features

#### A. RUB RAILS

installed on both sides of bodies for strap, side and stake pocket protection

## B. RUGGED 1/8" THICK TREAD PLATE FLOOR

#### C. B&W TURNOVERBALL®

rated at 30,000 lbs. gross trailer weight, with 7,500 lb. tongue weight

#### D. BOLT ON RECEIVER HITCH

Choose from 16K or 21K hitch, ordered separately to ship loose

## E. FORMED, INTEGRATED BULKHEAD

with stylized screened window and tapered design for improved visibility

#### F. 7-WAY TRAILER PLUG

at rear of body

#### G. DURABLE OVEN-CURED COAT

finish painted black

## H. ALL LED CLEARANCE AND MARKER LIGHTS

for visibility and added safety

## I. INTEGRATED OVAL LED B/U AND S/T/T LIGHTS

included in bulkhead and rear skirt

## J. SAFETY CHAIN ATTACHMENT POINTS

included with gooseneck hitch

#### A. SKIRTED GOOSENECK STYLING

with integrated front and rear toolboxes

#### **B. RUB RAILS**

installed on both sides of bodies for strap, side and stake pocket protection

## C. RUGGED 1/8" THICK TREAD PLATE FLOOR

with 6" structural channel long sills (4" on 8' models)

#### D. B&W TURNOVERBALL®

rated at 30,000 lbs. gross trailer weight, with 7,500 lb. tongue weight

#### E. BOLT ON RECEIVER HITCH

Choose from 16K or 21K hitch, ordered separately to ship loose

#### F. 7-WAY TRAILER PLUG

at rear of body

# G. SAFETY CHAIN ATTACHMENT POINTS

included with gooseneck hitch

#### **H.** DURABLE OVEN-CURED COAT

finish painted black

# I. ALL LED CLEARANCE AND MARKER LIGHTS

for visibility and added safety

# J. INTEGRATED OVAL LED B/U AND S/T/T LIGHTS

included in bulkhead and rear skirt

# K. CONTINUOUS STAINLESS STEEL HINGES

are pry-proof and corrosion-resistant

#### L. DOUBLE PANELED DOORS

consist of 20-gauge, two sided A-40 galvanneal steel

## M. AUTOMOTIVE QUALITY, ROTARY-STYLE LATCHES

make opening and closing easy

## FEATURES NOT SHOWN

12-GAUGE FORMED CROSS SILLS

INTEGRATED DRIVER SIDE FUEL FILL CUP

ELECTRODEPOSITION
PRIME-PAINT SYSTEM
provides superior corrosion
resistance

## FEATURES NOT SHOWN

12-GAUGE FORMED CROSS SILLS

**NEOPRENE DOOR SEALS** 

protect compartments from the weather

INTEGRATED DRIVER SIDE FUEL FILL CUP

ADJUSTABLE SECURITY RING STRIKERS

provide a weather-tight sea

**ELECTRODEPOSITION PRIME-PAINT SYSTEM**provides superior corrosion resistance

DOUBLE-SPRING OVER-CENTER DOOR RETAINER eliminates involuntary door swing

INTERIOR COVER protects internal latch from damage

4



#### A. DOUBLE PANELED DOORS

consist of 20-gauge, two sided A-40 galvanneal

#### **B. FLIP TOP COMPARTMENTS**

8" deep and with exterior release latch. Flip tops utilize nitrogen gas struts for smooth opening and closing

#### C. RUGGED 1/8" THICK TREAD **PLATE FLOOR**

D. 36" HIGH FRONT COMPARTMENTS each with 250 lb. capacity shelves

#### **E.** BOLT ON RECEIVER HITCH

Choose from 16K or 21K hitch, ordered separately to ship loose

#### F. FORMED, INTEGRATED BULKHEAD

with stylized screened window and tapered design for improved visibility

#### **G. 7-WAY TRAILER PLUG**

at the rear of the body

#### H. DURABLE OVEN-CURED COAT

finish painted black

#### I. ALL LED CLEARANCE AND **MARKER LIGHTS**

for visibility and added safety

#### J. UPGRADED REAR MOUNT LIGHTING SYSTEM

features LED S/T/T and B/U, LED strobe option\* with (8) selectable patterns, and built-in reflectivity for additional safety\*\*

\*Additional wire harness required for strobe lights \*\*Lights covered by 3-year limited warranty

#### K. CONTINUOUS STAINLESS STEEL HINGES

are pry-proof and corrosion-resistant

#### L. AUTOMOTIVE QUALITY. **ROTARY-STYLE LATCHES**

make opening and closing easy

#### M. FULL HEIGHT SLAM TAILGATE

with center mounted release handle

#### N. B&W TURNOVERBALL®

rated at 30,000 lbs. gross trailer weight, with 7,500 lb. tongue weight

#### O. GALVANNEAL FENDERETTES

are welded on

#### P. 7" DEEP REAR STEP

makes accessing cargo area safe and easy

## STYLING

with integrated front and rear toolboxes

**GOOSENECK BODIES** 

#### B. 36" HIGH FRONT COMPARTMENTS

**PGTE** 

each with 250 lb. capacity shelves

A. SKIRTED GOOSENECK

#### C. RUB RAILS

installed on both sides of bodies for strap, side and stake pocket protection

#### D. RUGGED 1/8" THICK TREAD **PLATE FLOOR**

#### E. B&W TURNOVERBALL®

rated at 30,000 lbs. gross trailer weight, with 7,500 lb. tongue weight

#### F. BOLT ON RECEIVER HITCH

Choose from 18K or 21K hitch, ordered separately to ship loose

#### **G.** 7-WAY TRAILER PLUG

at the rear of the body

#### H. SAFETY CHAIN **ATTACHMENT POINTS**

included with gooseneck hitch

#### I. DURABLE OVEN-CURED COAT finish painted black

#### J. ALL LED CLEARANCE AND **MARKER LIGHTS**

for visibility and added safety

#### K. INTEGRATED OVAL LED B/U **AND S/T/T LIGHTS**

included in bulkhead and rear skirt

#### L. CONTINUOUS STAINLESS **STEEL HINGES**

are pry-proof and corrosion-resistant

#### M. DOUBLE PANELED DOORS consist of 20-gauge, two sided A-40

galvanneal steel

#### N. AUTOMOTIVE QUALITY, **ROTARY-STYLE LATCHES**

make opening and closing easy

## FEATURES NOT SHOWN

12-GAUGE FORMED CROSS SILLS

250-LB. CAPACITY SHELVES MADE OF SPANGLED STEEL

**DOUBLE-SPRING OVER-CENTER DOOR RETAINER** ninates involuntary door swing **ELECTRODEPOSITION** PRIME-PAINT SYSTEM

provides superior corrosion

ADJUSTABLE SECURITY RING STRIKERS provide a weather-tight seal

**INTERIOR COVER** protects internal latch from damage

**NEOPRENE DOOR SEALS** 

#### 12-GAUGE FORMED CROSS SILLS

**NEOPRENE DOOR SEALS** protect compartments from the weather

DOUBLE-SPRING OVER-

CENTER DOOR RETAINER maintenance free door retained eliminates involuntary door swing **ADJUSTABLE SECURITY** RING STRIKERS

provide a weather-tight seal

**ELECTRODEPOSITION** PRIME-PAINT SYSTEM provides superior corrosion resistance

INTERIOR COVER protects internal latch from damage

FEATURES NOT SHOWN

7

\*Body may be shown with optional features

# PGTB / PGTC



ROUGHNECK CONTRACTOR **PACKAGE** 

Underbody toolboxes do not apply for PGTC



4" REMOVABLE SIDE BOARDS





3/16" TREAD PLATE FLOOR

# PGTD



**ADDITIONAL ALUMINUM** TREAD PLATE OVERLAY

**ABOVE BODY AND UNDERBODY TOOLBOXES** 

Underbody toolboxes do not apply for PGTC



3/16" TREAD PLATE FLOOR

## PGTE



3/16" TREAD PLATE FLOOR



**6" STAKE RACK SET** 

## POPULAR OPTIONS

# PGTD / PGTE



CTECH DRAWER SETS



**CARGO D-RINGS** 



LED COMPARTMENT LIGHTS





**POWER LOCKS** 




## **PGTB**

MODEL	LENGTH	WIDTH	WEIGHT	APPLICATION	SWING RADIUS	LONG SILL SPACING
PGTB-738-F	7'3"	84"	749 lb.	40" CA SRW	60"	38"
PGTB-868-F	8'6"	84"	844 lb.	56" CA SRW	60"	38"
PGTB-968	9'6"	84"	927 lb.	60" CA SRW	67"	34"
PGTB-86-F	8'6"	96"	904 lb.	56" CA DRW	63"	38"
PGTB-96	9'6"	96"	989 lb.	60" CA DRW	70"	34"
PGTB-116	11'6"	96"	1,144 lb.	84" CA DRW	70"	34"










## **PGTC**

MODEL	LENGTH	WIDTH	WEIGHT	APPLICATION	SWING RADIUS	LONG SILL SPACING
PGTC-738-F	7'3"	84"	936 lb.	40" CA SRW	60"	38"
PGTC-868-F	8'6"	84"	1,047 lb.	56" CA SRW	60"	38"
PGTC-9108	9'10"	84"	1,186 lb.	60" CA SRW	70"	34"
PGTC-86-F	8'6"	96"	1,148 lb.	56" CA DRW	63"	38"
PGTC-910	9'10"	96"	1,305 lb.	60" CA DRW	73"	34"
PGTC-1110	11'10"	96"	1,559 lb.	84" CA DRW	73"	34"










### **PGTD**

MODEL	LENGTH	WIDTH	WEIGHT	APPLICATION	SWING RADIUS	LONG SILL SPACING
PGTD-718-F	7'1"	80"	1,208 lb.	40" CA SRW	62"	38"
PGTD-848-F	8'4"	80"	1,367 lb.	56" CA SRW	61"	38"
PGTD-84-F	8'4"	96"	1,490 lb.	56" CA DRW	64"	38"
PGTD-948	9'4"	80"	1,510 lb.	60" CA SRW	72"	34"
PGTD-94	9'4"	96"	1,641 lb.	60" CA DRW	72"	34"
PGTD-114	11'4"	96"	1,969 lb.	84" CA DRW	72"	34"










## **PGTE**

MODEL	LENGTH	WIDTH	WEIGHT	APPLICATION	SWING RADIUS	LONG SILL SPACING
PGTE-738-F	7'3"	84.25"	940 lb.	40" CA SRW	60"	38"
PGTE-868-F	8'6"	84.25"	1,084 lb.	56" CA SRW	60"	38"
PGTE-9108	9'10"	84.25"	1,238 lb.	60" CA SRW	70"	34"
PGTE-86-F	8'6"	96"	1,182 lb.	56" CA DRW	63"	38"
PGTE-910	9'10"	96"	1,360 lb.	60" CA DRW	73"	34"
PGTE-1110	11'10"	96"	1,657 lb.	84" CA DRW	73"	34"







12



# THREE YEAR, LIMITED TIME WARRANTY







FREE FROM DEFECTS IN WORKMANSHIP



FREE FROM DEFECTS IN MATERIALS

TO LEARN MORE VISIT

www.knapheide.com/warranty



# **NEVER SETTLE**

If you are going to be a leader, it takes more than building a high-quality product. It means never being totally satisfied with that product, no matter how high quality it may be. It requires constant vigilance and a willingness to take a chance on something new. And it means exceeding expectations every time. As the industry changes, one thing never will—our commitment to making customers like you as productive and efficient as possible. We know you don't settle, and we don't either. That's why we want you never to settle for anything less than Knapheide on the back of your truck.

KNAPHEIDE. NEVER SETTLE.



The Knapheide Manufacturing Company 1848 Westphalia Strasse | Quincy, IL 62305 217-222-7131 www.knapheide.com